

Biogasclean QSR - **biological removal** of H₂S from biogas



Key features of Biogasclean QSR:

- **The PTU** – the Process Technique Unit - is the machine room and contains PLC controller board, circulation pump, air blower, valves, flow meters and – if required – also gas detector system and heating system installed either on a skid or in a custom built fiberglass container or a modified shipping container.
- **The scrubber tank** is manufactured in high quality fiberglass and supplied with a grating so it is possible to inspect the tank underneath the packing media. The tank is supplied with ladder and handrail and - if required – also with insulation. The tank is so strong that it can be filled with water. We manufacture fiberglass tanks in several countries to reduce transportation costs.
- **The packing media** is manufactured in plastic and can be cleaned inside the tank with the QSR® - Quick Sludge Removal - system. This will reduce downtime and increase revenues.
- **Safety**; injection of air into biogas is only safe with a reliable control system. The PLC receives signals from an oxygen meter and will reduce or stop air injection in case the oxygen content in the clean gas gets too high. If the PTU is enclosed the safety system will remove the ignition source by cutting the power supply if the gas detector in the PTU should measure above 25% of the Lower Explosive Level (LEL).

Plant: Thai Beverage Energy Co. Ltd
Thailand

Capacity: 600 m³/h
8,000 ppm H₂S





Plant: Iglsoe Agro & Biogas
Denmark

Capacity: 650 m³/h
(off-gas from
upgrading)
2,220 ppm H₂S

- **Automatic operation;** the system is automatically controlled by the PLC controller board which reduces the risk for manual errors and operation problems. The main function is to provide safe, optimal and stable conditions for the biological process. The signals can be made available in the control room.
- **Low operating costs;** the system uses no chemicals and has a very low electrical consumption. In many projects we use treated water from an anaerobic digester or an aeration pond as scrubber liquid and nutrient source. This is cheaper than soft water and industrial fertilizer. To prevent clogging inside the scrubber tank the water is first pre-treated in the MUW[®] - Make Up Water - system.
- **Guaranteed performance;** we provide performance guarantees on all projects.
- **Tailor made;** we design each system to the project specific biogas flow and H₂S load.

Biogasclean A/S

Biogasclean is specialized in biological desulfurization and methanation of biogas without the use, of chemicals. We develop, manufacture and supply fully automated gas cleaning systems for H₂S removal combining low operating costs with high availability. Our track record comprises more than 300 plants in operation or under construction in 40 countries. Biogasclean supplies clean gas to more than 650 MW gas engines and boilers and removes sulfur from more than 25 biogas upgrading plants for RNG production.

BIO
GASCLEAN | The key to innovative and
efficient production of biogas

Biogasclean A/S
Magnoliavej 10
DK-5250 Odense SV
Denmark
T (+45) 6617 2177
www.biogasclean.com

Biogasclean (Thailand Ltd.)
331 Moo 2, Unit S1/2
Soi Thetsaban Bangpoo 54
Sukhumvit Rd., T. Taiban, A. Muang
Samutprakarn 10270, Thailand
T (+66) (0)2 395-1157